

Series 2, Gas hob, 60 cm, Stainless steel PBP6B5B60



HEZ298105 Simmer plate HEZ298114 Small pot support

Gas hob with side-mounted controls: the desired cooking zones can be conveniently operated from the side.

- The seamless, one-piece stainless steel design makes cleaning simple
- Heavy-duty continuous surface grates can be easily and quickly cleaned in the dishwasher.

Appliance type: ga	as hob w integrated controls
Built-in / Free-standing:	Built-in
Heating type:	Gas
Number of cooking zones:	4
Type of control setting devices:	sword knobs
Min. required niche size for installation (H	HxWxD):45 x 560-562 x
480-492 mm	
Width of the appliance:	580 mm
Dimensions:	56x580x510 mm
Dimensions of the packed product (HxWx	:D): 141 x 651 x 578 mm
Net weight:	7.1 kg
Gross weight:	8.0 kg
Residual heat indicator:	without
Location of control panel:	Lateral
Basic surface material:	Stainless steel
Color of surface:	Stainless steel
Length electrical supply cord:	100.0 cm
EAN code:	4242002821221
Gas connection rating:	7400 W
Fuse protection:	3 А
Voltage:	220-240 V
Frequency:	60; 50 Hz





Series 2, Gas hob, 60 cm, Stainless steel PBP6B5B60

Gas hob with side-mounted controls: the desired cooking zones can be conveniently operated from the side.

Design

- Stainless steel surface
- cast iron finish pan supports with rubber feet

Usage convenience

- Design co-ordinated control dials: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 gas burners:
- Left front: high-speed burner up to 3 kW (depending on gas type)
- Left rear: Standard burner up to 1.7 KW (depending on gas type)
- Right rear: standard burner up to 1.7 KW (depending on gas type)
- Right front: economy burner up to 1 KW (depending on gas type)

Safety


- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): $56 \times 580 \times 510$
- Required niche size for installation (HxWxD mm) : $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.4 KW



Series 2, Gas hob, 60 cm, Stainless steel PBP6B5B60



- A: Min. distance from the hob cut-out to the wall
- **B**: Position of gas connection in the cut-out
- C: With fitted oven underneath possibly more; see space requirements for the oven